



*The TFP 260 Floor Scarifier is designed for medium to large applications with a 250mm operating width.*

## FEATURES

- Dead man switch
- Vacuum take off fitted
- Instant quick lift-off drum
- Metal protection for switch box
- Accurate **height adjustment** within 1mm
- **Solid rugged 8mm welded steel construction**
- **Choice of power source:** electric and petrol models available

## APPLICATIONS

- Reducing levels
- Grooving concrete
- Removal of old coatings
- Thermoplastic line removal



**Cleaning & keying concrete**



**Grooving drum**

A45 electric dust collector

**Part No: 303.4110 (110V)**

**Part No: 303.4220 (220V)**



**Use with A45 dust collector**

**TECHNICAL DATA**

	Petrol machine	Electric machine
<b>Part No.</b>	<b>326.2000T</b>	<b>326.2006T</b>
<b>Specifications</b>		
Working width	250 mm	250 mm
Output power	8 Hp / 6 kW	7.5 Hp / 5.5 kW
Cutter speed (rpm)	1500	1500
Max. cutting width	Up to 250 mm	Up to 250 mm
Vibration level	8.80 m/s <sup>2</sup>	2.40 m/s <sup>2</sup>
Usage	2 to 8 hours	2 to 8 hours
<b>Supply requirements</b>		
Voltage	-	415 V
Phase	-	Three
Cycle	-	50 / 60 Hz
Plug size	-	16 Amp 5 pin
Cable size (mm)	-	Min. 2.5 mm <sup>2</sup> core
Cable length	-	30 m
Engine type	Honda GX240 (4 stroke)	-
<b>Dimensions</b>		
Length	1120 mm	1120 mm
Width	440 mm	440 mm
Height	1160 mm	1160 mm
Weight	185 Kg	185 Kg

-All part number specified above are for machines complete with tungsten carbide tipped cutters. For machines requiring alternative cutting media please specify.

**Accessory guide vs. applications**

Various types of cutters are available to suit all the different kinds of applications



**Tungsten Carbide Tipped Cutter –**  
for all concrete texturing, scabbling, planing and grooving applications



**Star Cutters –**  
for the removal of paint, coatings and laitance. Deck descaling



**Beam Cutters –**  
for the removal of paint, coatings, laitance, grease, dirt and ice deposits. Deck descaling



**Milling Cutter –**  
for the removal of thermoplastic road and runway markings, bituminous and rubber deposits

*see separate accessory sheet for cutter & drum options*



Always look for the Vibro-Lo label on tools designed to reduce the risk of vibration related injuries