

SCALEFORCE PNEUMATIC HANDHELD SCALING HAMMERS

SF



TRELAWNY'S SF RANGE OF SCALING HAMMERS ARE HIGHLY EFFECTIVE FOR QUICK REMOVAL OF HEAVY SCALE AND COATINGS

The SF1/VLSF1 single head tools are perfect for smaller and awkward to reach areas, being lightweight and easy to handle, it's perfect for reaching behind structures and up against bulkheads.

The SF3 three head tools give faster production for more open areas.



Low vibration options available



Non spark options available

FEATURES & BENEFITS

- Option of replaceable carbide tipped scaling heads or economical hardened steel single piece pistons
- Beryllium copper spark resistant heads for use in potentially explosive environments
- Ergonomic handle for ease of use – also available with a short handle and/or inline for tight areas
- Simple and robust design for low and easy maintenance

APPLICATIONS

- Quick removal of heavy coatings and rust
- Preparation before blasting
- Cleaning pipes



CORROSION REMOVAL



SHIPYARDS MANAGEMENT







RUST DE SCALING

SCALEFORCE PNEUMATIC HANDHELD SCALING HAMMERS


SF

KEY CONSUMABLES & ACCESSORIES

Image	Part Number	Description
	426.5351	Cruciform Taper fit Cutter Head Tungsten carbide tipped head - for fracturing and removal of coatings To fit 151.5100 / 196.5095 / 153.5300
	606.5303	Cruciform Taper fit Cutter Head Beryllium copper spark resistant - for fracturing and removal of coatings To fit 151.5110 / 153.5310 
	426.5352	Bush Hammer Taper fit Cutter Head Tungsten carbide tipped head - creates a heavier key on the surface To fit 151.5105 / 153.5305
	612.5301	Piston to fit Cutter Heads

Image	Part Number	Description
	859.1555	1/2 Inline Lubricator
	815.5550	Whip Check
	458.1555	Whip Hose & Oiler Assembly Consists of whip hose, whip check and 1/2 inline lubricator
	614.5301	Brush Seal

TECHNICAL DATA

Model	Part No.	Consumable (type of head)	Weight (kg)	Length (mm)	Working height (mm)	Blows per minute (BPM)	Air consumption (lps - cfm)	Noise level (db (A))	Vibration Level (Aeq m/s ²)
Single Head	151.5100	Cruciform head	2.5	465	152.5	3000	3.3 - 7	88.1	6.8
Single Head	151.5110	Beryllium copper taper fit cutter	2.5	465	152.5	3000	3.3 - 7	88.1	6.8
Single Head	151.5180	Single piece steel piston	2.5	465	152.5	3000	3.3 - 7	88.1	6.8
Vibro-Lo™ Single Head	196.5095	Cruciform head	2.5	515	140	3000	4.25 - 9	92.5	3.7 
Triple Head	153.5300	Cruciform head	3.7	450	152.5	3000 x 3	5.2 - 11	92.7	13.4
Triple Head	153.5310	Beryllium copper taper fit cutter	3.7	450	152.5	3000 x 3	5.2 - 11	92.7	13.4
Triple Head	153.5380	Single piece steel piston	3.7	450	152.5	3000 x 3	5.2 - 11	92.7	13.4